



LEADING INDIA'S CARGO FLEET ELECTRIFICATION



AVAILABLE IN THREE
VARIANTS

FLAT BED
HALF LOADER
FULL LOADER



EXPLORE THE SOLID POWER OF A BULL

Etrio is a tech-driven EV-maker with the vision to "lead cargo fleet electrification". Touro, is derived from the word "Toro" which means a bull. The design philosophy, thus, emulates the attributes of a bull such as strong stability, unmatched power, immense load carrying capacity, relentless work ethic and intense focus.



UNMATCHED SAFETY



- ⚡ HYDRAULIC BRAKES
- ⚡ WIDER TIRES FOR SUPERIOR ROAD GRIP.
- ⚡ BEST IN CLASS SHEET METAL BODY
- ⚡ HIGHER LEVEL OF WATER AND DUST PROTECTION (IP65)



SUPERIOR PERFORMANCE

- ⚡ PAYLOAD OF UPTO 550 KG
- ⚡ VOLUMETRIC CAPACITY OF UPTO 130 CUFT
- ⚡ MOTOR POWER OF 9.5KW AND TORQUE OF 60. NM- BEST IN CLASS
- ⚡ TOP SPEED OF 50 KMPH

THE POWER OF PLENTY.

SAVINGS BOOSTER



- ⚡ UPTO RS 70000 SAVINGS PER YEAR
- ⚡ RUNNING COST SAVINGS OF RS 2.3 PER KM
- ⚡ MAINTENANCE ONLY RS 0.7 PER KM
- ⚡ NO ROAD TAX AND REGISTRATION COST
- ⚡ ZERO MAINTENANCE BATTERY

COMFORT AND CONVENIENCE



- ⚡ INDEPENDENT SUSPENSION -BEST IN CLASS
- ⚡ HOME CHARGING-IS A CHARGER.
- ⚡ COMFORTABLE SEATS
- ⚡ AMPLE STORAGE SPACE

FUTURISTIC DESIGN



- ⚡ DUAL HEADLAMP*
- ⚡ BULL INSPIRED SIGNATURE FRONT GRILLE

ETRIO CARE - BEST IN CLASS WARRANTY



- ⚡ BATTERY WARRANTY 100000 KM*
- ⚡ POWERTRAIN WARRANTY UP TO 100000 KM*
- ⚡ AUXILIARY WARRANTY UP TO 60000 KM*

ADVANCED TECHNOLOGY



- ⚡ ADVANCED LITHIUM-ION BATTERY
- ⚡ CLOUD BASED E-MOBILITY- TELEMATICS
- ⚡ STATE OF ART DIGITAL CLUSTER
- ⚡ REGENERATIVE HYDRAULIC BRAKES

READY TO MANOEUVRE THE MIGHTY BULL?

- ⚡ AUTOMATIC CLUTCH-LESS DRIVE
- ⚡ OPERATIONAL COST SAVINGS OF ALMOST 70%
- ⚡ BEST IN CLASS PERFORMANCE IN TERMS OF RANGE AND VOLUMETRIC CAPACITY

TECHNICAL SPECIFICATIONS:

Model	TUORO MAX++
Vehicle Category	LSN
Warranty	
Vehicle Warranty (Years)*	3
Battery Warranty (Years)*	3
Warranty (Km)*	100000
Vehicle Specifications	
Length (mm)	3140
Width (mm)	1470
Height (mm)	1740
Wheelbase (mm)	1970
Gross Vehicle Weight (kg)	950
Ground Clearance (mm)	180
Tyre Size	4.5*10"
Top Speed (kmph)	50
Front Brake	Drum
Rear Brake	Drum
Front Suspension	Coil Spring with Telescopic Shock Absorber
Rear Suspension	Rubber Boot with Telescopic Shock Absorber
Transmission Type	Independent Drive
Gradeability (%)	12.5
Load Body Specifications	
Length (mm)	1730
Width (mm)	1450
Height (mm)	1500
Pay Load (Kg)	550
Cargo Volume (cu.ft)	130
Power Train Specifications	
Battery (kwh)	10.8
Motor Architecture	PMSM
Max Power (kW)	9.5
Peak Torque (Nm)	63
Range (km)*	157
Drive Modes	Eco, Boost & Reverse
48V Charger Specification	3kW or 40A
Charging Time AC (hrs)	4

* T&C APPLY



Contact Details :

For Bookings :
Website : www.etr.io
Email : hello@etr.io

Please note that the images and technical specifications shown in the chart may showcase accessories and equipment which are not part of the standard fitment. E-Trio reserves the rights to alter the technical specifications are subject to improvements / changes.